

ARB AIR COMPRESSORS - TECHNICAL SPECIFICATIONS

MODEL NUMBER/DESCRIPTION	SUPPLY VOLTAGE	CURRENT DRAW NO-LOAD	AIR FLOW UNDER NO-LOAD		CURRENT DRAW UNDER LOAD	AIR FLOW UNDER LOAD		WEIGHT compressor & included accessories		DUTY CYCLE % @ 22°C (72°F) (ON TIME / OFF TIME)	SIZE mm [inches] portable compressor sizes shown as carry case size			AUTOMOTIVE LOAD PROTECTION IN LOOM	AIR LOCKER SOLENOID MOUNTING MANIFOLD	PRESSURE CUTOFF SWITCH	DURABLE POLYPROPYLENE CARRY CASE	AIR FILTER EQUIPPED	6 METRE (20 FT) TYRE INFLATION HOSE	THERMAL OVER-LOAD PROTECTED MOTOR
			@ 0KPa	@ 0PSI		@ 200KPa	@ 29PSI	Kgs	Lbs		Height	Length	Width							
CKMP12 High Output Portable	12	14A	87.2L/m	3.08CFM	25A	66L/m	2.34CFM	6.6	14.5	50% 30/30	208mm [8.2"]	440mm [17.3"]	238mm [9.4"]	YES	NO	YES	YES	YES	YES	YES
CKMTP12 Twin Motor Portable	12	28A	174.4L/m	6.16CFM	50A	132L/m	4.68CFM	15	33	100% 60/0	186mm [7.3"]	478mm [18.8"]	355mm [14"]	YES	NO	YES	YES	YES	YES	YES
CKSA12 Compact On-Board	12	5.5A	27.7L/m	0.98CFM	7.5A	19.7L/m	0.70CFM	2.4	5.3	35% 21/39	122mm [4.8"]	162mm [6.4"]	88mm [3.5"]	NO	YES	YES	N/A	YES	NO	NO
CKMA12 High Output On-Board	12	14A	87.2L/m	3.08CFM	25A	66L/m	2.34CFM	4.5	9.9	50% 30/30	145mm [5.7"]	190mm [7.5"]	98mm [3.9"]	YES	YES	YES	N/A	YES	NO	YES
CKMA24 High Output On-Board	24	7A	87.2L/m	3.08CFM	12.6A	66L/m	2.34CFM	4.5	9.9	50% 30/30	145mm [5.7"]	190mm [7.5"]	98mm [3.9"]	YES	YES	YES	N/A	YES	NO	YES
CKMTA12 Twin Motor On-Board	12	28A	174.4L/m	6.16CFM	50A	132L/m	4.68CFM	8.8	19.4	100% 60/0	105mm [4.1"]	278mm [10.9"]	190mm [7.5"]	YES	NO	YES	N/A	YES	NO	YES
CKMTA24 Twin Motor On-Board	24	14A	174.4L/m	6.16CFM	25A	132L/m	4.68CFM	8.8	19.4	100% 60/0	105mm [4.1"]	278mm [10.9"]	190mm [7.5"]	YES	NO	YES	N/A	YES	NO	YES